MITIGATION MONITORING PROGRAM

Section 21081.6 of the Public Resources Code requires a Lead Agency to adopt a "reporting or monitoring program for the changes made to the project or conditions of project approval, adopted in order to mitigate or avoid significant effects on the environment" (Mitigation Monitoring Program, Section 15097 of the *CEQA Guidelines* provides additional direction on mitigation monitoring or reporting). This Mitigation Monitoring Program (MMP) has been prepared in compliance with the requirements of CEQA, Public Resources Code Section 21081.6, and Section 15097 of the CEQA Guidelines. The City of Los Angeles is the Lead Agency for this project.

A Sustainable Communities Environmental Assessment (SCEA) has been prepared to address the potential environmental impacts of the Project. Where appropriate, this environmental document identified Project design features, regulatory compliance measures, or recommended mitigation measures to avoid or to reduce potentially significant environmental impacts of the Proposed Project. This Mitigation Monitoring Program (MMP) is designed to monitor implementation of the mitigation measures identified for the Project.

The MMP is subject to review and approval by the City of Los Angeles as the Lead Agency as part of the approval process of the project, and adoption of project conditions. The required mitigation measures are listed and categorized by impact area, as identified in the SCEA.

The Project Applicant shall be responsible for implementing all mitigation measures, unless otherwise noted, and shall be obligated to provide documentation concerning implementation of the listed mitigation measures to the appropriate monitoring agency and the appropriate enforcement agency as provided for herein. All departments listed below are within the City of Los Angeles unless otherwise noted. The entity responsible for the implementation of all mitigation measures shall be the Project Applicant unless otherwise noted. As shown on the following pages, each required mitigation measure for the proposed Project is listed and categorized by impact area, with accompanying discussion of:

Enforcement Agency – the agency with the power to enforce the Mitigation Measure.

- Monitoring Agency the agency to which reports involving feasibility, compliance, implementation and development are made, or whom physically monitors the project for compliance with mitigation measures.
- Monitoring Phase the phase of the Project during which the Mitigation Measure shall be monitored.
 - Pre-Construction, including the design phase
 - Construction
 - Pre-Operation
 - Operation (Post-construction)

- Monitoring Frequency the frequency of which the Mitigation Measure shall be monitored.
- Action Indicating Compliance the action of which the Enforcement or Monitoring Agency indicates that compliance with the required Mitigation Measure has been implemented.

The MMP performance shall be monitored annually to determine the effectiveness of the measures implemented in any given year and reevaluate the mitigation needs for the upcoming year.

It is the intent of this MMP to:

Verify compliance of the required mitigation measures of the SCEA;

Provide a methodology to document implementation of required mitigation;

Provide a record and status of mitigation requirements;

Identify monitoring and enforcement agencies;

Establish and clarify administrative procedures for the clearance of mitigation measures;

Establish the frequency and duration of monitoring and reporting; and

Utilize the existing agency review processes' wherever feasible.

This MMP shall be in place throughout all phases of the proposed Project. The entity responsible for implementing each mitigation measure is set forth within the text of the mitigation measure. The entity responsible for implementing the mitigation shall also be obligated to provide certification, as identified below, to the appropriate monitoring agency and the appropriate enforcement agency that compliance with the required mitigation measure has been implemented.

After review and approval of the final MMP by the Lead Agency, minor changes and modifications to the MMP are permitted, but can only be made by the Applicant or its successor subject to the approval by the City of Los Angeles through a public hearing. The Lead Agency, in conjunction with any appropriate agencies or departments, will determine the adequacy of any proposed change or modification. The flexibility is necessary in light of the proto-typical nature of the MMP, and the need to protect the environment with a workable program. No changes will be permitted unless the MMP continues to satisfy the requirements of CEQA, as determined by the Lead Agency.

MITIGATION MONITORING PROGRAM

Biological Resources

MM BIO-1: Prior to the issuance of any permit, a plot plan shall be prepared indicating the location, size, type, and general condition of all existing trees on the site and within the adjacent public right(s)-of way.

MM BIO-2: Removal or planting of any tree in the public right-of-way requires approval of the Board of Public Works. Contact Urban Forestry Division at 213-847-3077. All trees in the public right-of-way shall be provided at a 2 to 1 ratio per the standards of the Urban Forestry Division, Bureau of Street Services, Department of Public Works.

Enforcement Agency: Los Angeles Department of Building and Safety

Monitoring Agency: Los Angeles Department of Building and Safety

Monitoring Phase: Construction

Monitoring Frequency: Once, prior to issuance of building permit; or, if vegetation removal, building demolition or grading is initiated during the nesting season, as determined by a qualified biologist

Action Indicating Compliance: if vegetation removal, building demolition, or grading is initiated during the nesting season, submittal of a survey report by a qualified biologist.

MM BIO-III Habitat Modification (Nesting Native Birds, Non-Hillside or Urban Areas) The project will result in the removal of vegetation and disturbances to the ground and therefore may result in take of nesting native bird species. Migratory nongame native bird species are protected by international treaty under the Federal Migratory Bird Treaty Act (MBTA) of 1918 (50 C.F.R Section 10.13). Sections 3503, 3503.5 and 3513 of the California Fish and Game Code prohibit take of all birds and their active nests including raptors and other migratory nongame birds (as listed under the Federal MBTA).

- Proposed project activities (including disturbances to native and non-native vegetation, structures and substrates) should take place outside of the breeding bird season which generally runs from March 1- August 31 (as early as February 1 for raptors) to avoid take (including disturbances which would cause abandonment of active nests containing eggs and/or young). Take means to hunt, pursue, catch, capture, or kill, or attempt to hunt, pursue, catch, capture of kill (Fish and Game Code Section 86).
- If project activities cannot feasibly avoid the breeding bird season, beginning thirty days prior to the disturbance of suitable nesting habitat, the applicant shall:

- a. Arrange for weekly bird surveys to detect any protected native birds in the habitat to be removed and any other such habitat within properties adjacent to the project site, as access to adjacent areas allows. The surveys shall be conducted by a qualified biologist with experience in conducting breeding bird surveys. The surveys shall continue on a weekly basis with the last survey being conducted no more than 3 days prior to the initiation of clearance/construction work.
- b. If a protected native bird is found, the applicant shall delay all clearance/construction disturbance activities within 300 feet of suitable nesting habitat for the observed protected bird species until August 31.
- c. Alternatively, the Qualified Biologist could continue the surveys in order to locate any nests. If an active nest is located, clearing and construction within 300 feet of the nest or as determined by a qualified biological monitor, shall be postponed until the nest is vacated and juveniles have fledged and when there is no evidence of a second attempt at nesting. The buffer zone from the nest shall be established in the field with flagging and stakes. Construction personnel shall be instructed on the sensitivity of the area.
- d. The applicant shall record the results of the recommended protective measures described above to document compliance with applicable State and Federal laws pertaining to the protection of native birds. Such record shall be submitted and received into the case file for the associated discretionary action permitting the project.

Enforcement Agency: Los Angeles Department of Building and Safety

Monitoring Agency: Los Angeles Department of Building and Safety

Monitoring Phase: Construction

Monitoring Frequency: Once, prior to issuance of building permit; or, if vegetation removal, building demolition or grading is initiated during the nesting season, as determined by a qualified biologist

Action Indicating Compliance: if vegetation removal, building demolition, or grading is initiated during the nesting season, submittal of a survey report by a qualified biologist.

Cultural Resources

MM CULT-1: Prior to the issuance of a demolition permit, the Applicant shall retain a qualified Archaeologist who meets the Secretary of the Interior's Professional Qualifications Standards (qualified Archaeologist) to oversee an archaeological monitor who shall be present during construction activities on the Project Site such as demolition, clearing/grubbing, grading, renching, or any other construction excavation activity associated with the Project. The activities to be monitored shall also include off-site improvements in the vicinity of the Project Site that involve ground disturbance, such as utility, sidewalk, or road improvements which would encounter soils that could potentially contain archaeological resources down to a depth of 5-feet. The monitor shall have the authority to direct the pace of construction equipment in areas of

higher sensitivity. The frequency of monitoring shall be based on the rate of excavation and grading activities, the materials being excavated (younger sediments vs. older sediments), and the depth of excavation, and if found, the abundance and type of archaeological resources encountered. Full-time monitoring may be reduced to part-time inspections, or ceased entirely, if determined adequate by the qualified Archaeologist. Prior to commencement of excavation activities, an Archaeological Sensitivity Training shall be given for construction personnel. The training session, shall be carried out by the qualified Archaeologist, will focus on how to identify archaeological resources that may be encountered during earthmoving activities, and the procedures to be followed in such an event.

MM CULT-2: In the event that historic (e.g., bottles, foundations, refuse dumps/privies, railroads, etc.) or prehistoric (e.g., hearths, burials, stone tools, shell and faunal bone remains, etc.) archaeological resources are unearthed, ground-disturbing activities shall be halted or diverted away from the vicinity of the find so that the find can be evaluated. A 25-foot buffer shall be established by the qualified Archaeologist around the find where construction activities shall not be allowed to continue. Work shall be allowed to continue outside of the buffer area. All archaeological resources unearthed by Project construction activities shall be evaluated by the qualified Archaeologist. If a resource is determined by the qualified Archaeologist to constitute a "historical resource" pursuant to State CEQA Guidelines Section 15064.5(a) or a "unique archaeological resource" pursuant to PRC Section 21083.2(g), the qualified Archaeologist shall coordinate with the Applicant and the City to develop a formal treatment plan that would serve to reduce impacts to the resources. If any prehistoric archaeological sites are encountered within the project area, consultation with interested Native American parties will be conducted to apprise them of any such findings and solicit any comments they may have regarding appropriate treatment and disposition of the resources. The treatment plan established for the resources shall be in accordance with State CEQA Guidelines Section 15064.5(f) for historical resources and PRC Sections 21083.2(b) for unique archaeological resources. Preservation in place (i.e., avoidance) is the preferred manner of treatment under CEQA. If in coordination with the City, it is determined that preservation in place is not feasible, appropriate treatment of the resource shall be developed by the qualified Archaeologist in coordination with the City and may include implementation of archaeological data recovery excavations to remove the resource along with subsequent laboratory processing and analysis. Any archaeological material collected shall be curated at a public, non-profit institution with a research interest in the materials, if such an institution agrees to accept the material. If no institution accepts the archaeological material, they shall be donated to a local school or historical society in the area for educational purposes.

MM CULT-3: Prior to the release of the grading bond, the qualified Archaeologist shall prepare a final report and appropriate California Department of Parks and Recreation Site Forms at the conclusion of archaeological monitoring. The report shall include a description of resources unearthed, if any, treatment of the resources, results of the artifact processing, analysis, and research, and valuation of the resources with respect to the California Register of Historical Resources and CEQA. The report and the Site Forms shall be submitted by the Project Applicant to the City, the South Central Coastal Information Center, and representatives of other appropriate or concerned agencies to signify the satisfactory completion of the development and required mitigation measures. **Enforcement Agency:** Los Angeles Department of Building and Safety and Los Angeles Department of City Planning

Monitoring Agency: Los Angeles Department of Building and Safety

Monitoring Phase: Pre-Construction

Monitoring Frequency: Once, prior to issuance of building permit

Action Indicating Compliance: issuance of applicable building permit

Hazards and Hazardous Materials

MM HAZ-1: A Site Specific Soil Mitigation Plan (SMP) will be prepared that will provide guidance to contractors for appropriate handling, screening, and management of potentially impacted or impacted soils that may be encountered at the Project Site during grading and excavation activities. These procedures will include training for construction personnel on the appropriate procedures for identification of suspected impacted soils; requirements for testing and collection of potentially contaminated soils; segregation of potentially impacted soils; and applicable soil handling and disposal procedures. The SMP will also include procedures for handling and transportation of soils with respect to nearby sensitive receptors, such as nearby residential uses and schools. In accordance with SCAQMD Rule 1166 requirements, impacted soil removed from the Project Site must comply with the following: Be transported to an approved treatment/disposal facility, When loading into trucks is completed, and during transportation, no excavated material will extend above the sides or rear of the truck or trailer, Prior to covering/tarping, loaded impacted soil must be wetted by spraying with dust inhibitors, The trucks or trailers must be completely covered/tarped prior to leaving the Project Site to prevent particulate emissions to the atmosphere, and The exterior of the trucks (including the tires) must be cleaned off prior to the trucks leaving the excavation location and leaving the disposal site before returning to the Project Site.

MM HAZ-2: A Groundwater Management Plan (GWMP) will be prepared that includes training and protocol procedures to contractors for avoiding contact with groundwater during excavation and construction of the Project and appropriate disposal protocols of contaminated groundwater. The GWMP will include a requirement for development and implementation of a safety plan to be prepared prior to commencement of construction consistent with Occupational Safety and Health Administration (OSHA) Safety and Health Standards 29 CFR 1910.120 as well as management of groundwater produced through temporary dewatering activities. The safety plan will include necessary training, operating and emergency response procedures, and reporting requirements to regulate all activities that bring workers in contact with potentially contaminated groundwater. In the unlikely event that groundwater contamination occurs, the GWMP will include remedial efforts that may include batch extraction of groundwater using an on-site dewatering system or application of a chemical amendment, such as oxygen or hydrogen source depending on the type of contamination impact. **MM HAZ-3:** All concrete cuts and utility penetrations into the building pad(s) or concrete slab(s) that underlie the former church building that may occur during the remodeling/repurposing of the existing school building will be sealed to add an additional measure of protection against potential vapor intrusion.

Enforcement Agency: Los Angeles Department of Building and Safety

Monitoring Agency: Los Angeles Department of Building and Safety

Monitoring Phase: Construction and Operation

Monitoring Frequency: Ongoing

Action Indicating Compliance: None – ongoing operational compliance required.

Noise

MM NOISE-1: The Project shall implement construction noise reduction strategies to reduce noise levels from construction affecting the noise sensitive residential receptors located to the east of the Project Site, with a performance standard of achieving a construction noise level of less than 66 dBA Leg at the noise-sensitive residential receptors adjacent to the east of the Project Site. The noise reduction strategies shall include one or a combination of the following to achieve the performance standard. Use construction equipment, fixed or mobile, that individually generates less noise than presumed in the Federal Highway Administration (FHWA) Roadway Construction Noise Model (RCNM). Examples of such equipment are medium, compact, small, or mini model versions of backhoes, cranes, excavators, loaders, or tractors; or newer model equipment; or other applicable equipment that are equipped with reduced noise-generating engines. Construction equipment noise levels shall be documented based on manufacturer's specifications. The construction contractor shall keep construction equipment noise level documentation on-site for the duration of Project construction. Noise-generating equipment operated at the Project Site shall be equipped with California industry standard noise control devices to effectively reduce noise levels, i.e., mufflers, lagging, and/or motor enclosures. All equipment shall be properly maintained to assure that no additional noise, due to worn or improperly maintained parts, would be generated. The reduction in noise level from noise shielding and muffling devices shall be documented based on manufacturer's specifications. The construction contractor shall keep noise shielding and muffling device documentation on-site and documentation demonstrating that the equipment has been maintained in accordance with the manufacturers' specifications on-site for the duration of Project construction. Construction and demolition activities shall be scheduled so as to minimize or avoid operating multiple heavy pieces of equipment such as a large dozer, concrete saw, and excavator, simultaneously at the perimeter of the Project Site along the eastern boundary of the Project Site. The Project shall provide temporary minimum 8-foot-tall construction noise barriers along property lines facing adjacent off-site residential buildings to the east and northeast. The temporary barriers shall at a minimum remain in place during early Project construction phases (up to the start of framing) when the use of heavy equipment is prevalent. Standard construction protective fencing with green screen or pedestrian barricades for protective walkways shall be installed along property

lines facing streets or commercial buildings. All temporary barriers, fences, and walls shall have gate access as needed for construction activities, deliveries, and site access by construction personnel. The Project shall offer noise mitigation measures to the residential units located directly adjacent to the eastern boundary of the Project Site for those residential units in which the temporary construction noise barrier would not block the line-of-sight between the construction equipment and the residential unit windows facing the Project Site. These mitigation measures may include installation of temporary vertical sheeting at noise-sensitive points, such as residential unit windows facing the Project Site, to provide noise attenuation. The Project shall stage noise-generating construction equipment as far away from the noise-sensitive receptors adjacent to the east of the Project Site as practicable; minimize the number of noisegenerating construction equipment in simultaneous use; and/or provide other noise-reducing techniques. The effectiveness of the noise reduction strategies to achieve the performance standard shall be documented by on-site noise monitoring conducted by a qualified acoustical analyst using a Type 1 instrument in accordance with the American National Standards Institute (ANSI) S1.4. Noise monitoring shall be conducted during early Project construction phases when the use of heavy equipment is prevalent.

MM NOISE-2: The Applicant shall designate a construction relations officer to serve as a liaison with surrounding residents and property owners who is responsible for responding to any concerns regarding construction noise and vibration. The liaison's telephone number(s) shall be prominently displayed at the Project Site. Signs shall also be posted at the Project Site that include permitted construction days and hours.

MM NOISE-3: The Project shall install a sound enclosure or equivalent noise attenuation measures for the Project's operational emergency generators that shall provide a minimum noise reduction of 15 dBA. The generator would generate noise levels of approximately 81 dBA (Leq) at 25 feet with the noise attenuation measures. At Plan Check, building plans shall include documentation prepared by a noise consultant verifying compliance with this measure.

MM NOISE-4: The Project shall implement construction vibration reduction strategies to reduce vibration levels from construction affecting vibration sensitive receptors to the east of the Project Site, with a performance standard of achieving a construction vibration level of less than 0.5 inches per second PPV at the face of the on-site former church building, less than 0.3 inches per second PPV at the face of the 3109 West 6th Street building and the 523 South Westmoreland Avenue building, and 72 VdB or less at occupied vibration-sensitive residential receptors adjacent to the east of the Project Site.

MM NOISE-5: Prior to construction, the Applicant shall retain the services of a qualified acoustical/vibration engineer to review the proposed construction equipment and develop and implement a vibration monitoring program capable of documenting the construction-related ground vibration levels at the on-site former church building, the 3109 West 6th Street building, and the 523 South Westmoreland Avenue building. The Applicant and qualified acoustical/vibration engineer shall conduct a pre-construction survey that visually identifies the existing conditions of the on-site former church building, the 3109 West 6th Street building, and the 523 South Westmoreland Avenue building. During construction, the contractor shall install and maintain at least one continuously operational automated vibrational monitors on the on-site

former church building, the 3109 West 6th Street building, and the 523 South Westmoreland Avenue building. The monitoring system shall produce real-time specific alarms (for example, via text message and/or email to on-site personnel) when velocities exceed either of the predetermined levels. In the event of a first-level alarm, feasible steps to reduce vibratory levels shall be undertaken, including but not limited to halting/staggering concurrent activities and utilizing lower-vibratory techniques. In the event of an exceedance of the threshold level, the contractor shall review the construction work in the vicinity and investigate construction methods that would reduce vibration levels in the vicinity. If it is determined that the construction work is causing an exceedance of the vibration threshold level, the contractor shall also visually inspect the on-site former church building, the 3109 West 6th Street building, and the 523 South Westmoreland Avenue building for damage. Results of the inspection shall be logged. In the event damage occurs to finish materials due to construction vibration, such materials shall be repaired in consultation with a qualified preservation consultant, and if warranted, in a manner that meets the Secretary of the Interior's Standards.

MM NOISE-6: Prior to the issuance of grading permits, the Applicant will provide a shoring plan prepared by a qualified structural engineer who meets the relevant Secretary of the Interior's Professional Standards, for review and approval by the City of Los Angeles. The shoring plan will ensure the protection of the on-site former church building on the Project Site, as well as the potential historic resources adjacent to the Project Site at 3109 West 6th Street and 523 South Westmoreland Avenue, during construction.

Enforcement Agency: Los Angeles Department of Building and Safety

Monitoring Agency: Los Angeles Department of Building and Safety

Monitoring Phase: Construction

Monitoring Frequency: Ongoing during field inspection

Action Indicating Compliance: Issuance of Certificate of Occupancy or Use of Land

Public Services

MM PS-1

A construction fence will be constructed around the Project Site to minimize trespassing, vandalism, short-cut attractions and attractive nuisances.

MM PS-2

Environmental impacts may result from project implementation due to the location of the project in an area having marginal police services. However, this potential impact will be mitigated to a less than significant level by the following measure: • The plans shall incorporate the design guidelines relative to security, semi-public and private spaces, which may include but not be limited to access control to building, secured parking facilities, walls/fences with key systems, well-illuminated public and semi-public space designed with a minimum of dead space to eliminate areas of concealment, location of toilet facilities or building entrances in high-foot traffic areas, and provision of security guard patrol throughout the project site if needed. Please refer to "Design Out Crime Guidelines: Crime Prevention Through Environmental Design", published by the Los Angeles Police Department. Contact the Community Relations Division, located at 100 W. 1st Street, #250, Los Angeles, CA 90012; (213) 486-6000. These measures shall be approved by the Police Department prior to the issuance of building permits.

MM PS-3

Prior to the occupancy of the Project, the Applicant will provide the Olympic Area Commanding Officer with a diagram of each portion of the property, including access routes, and additional information to facilitate potential LAPD responses.

Enforcement Agency: Los Angeles Department of Building and Safety

Monitoring Agency: Los Angeles Department of Building and Safety

Monitoring Phase: Pre-Construction

Monitoring Frequency: Once, at plan check

Action Indicating Compliance: Issuance of building permits

Transportation and Traffic

MM-TRAF-1: The Applicant shall prepare a detailed Construction Management Plan that shall include, but not be limited to, the following elements, as appropriate: Requiring workers and construction trucks to generally travel outside of the peak hours Prohibition of construction worker parking on nearby residential streets, Temporary traffic control during all construction activities encroaching on public rights-of-way to improve traffic flow and safety on public roadways, Scheduling of construction activities to reduce the effect on traffic flow on surrounding arterial streets, Safety precautions for pedestrians and bicyclists through such measures as alternate routing and protection barriers as appropriate, Scheduling of construction-related deliveries so as to generally occur outside the commuter peak hours, Installation of appropriate traffic signs around the Project Site to ensure pedestrian, bicycle, and vehicle safety.

To further reduce any construction related conflicts near schools, the following Project specific mitigation measures are included:

MM TRAF-2: There shall be no staging or parking of construction vehicles, including vehicles to transport workers on any of the streets adjacent to the school.

MM TRAF-3: LADBS shall assign specific haul route hours of operation based upon Young Oak Kim Academy's hours of operation.

MM TRAF-4: Haul route scheduling shall be sequenced to minimize conflicts with pedestrians, school buses and cars at the arrival and dismissal times of the school day. Haul route trucks shall not be routed past the school during periods when school is in session especially when students are arriving or departing from the campus.

MM TRAF-5: The Applicant shall plan construction and construction staging as to maintain pedestrian access on adjacent sidewalks throughout all construction phases. This requires the applicant to maintain adequate and safe pedestrian protection, including physical separation (including utilization of barriers such as K-Rails or scaffolding, etc.) from work space and vehicular traffic and overhead protection, due to sidewalk closure or blockage, at all times. Temporary pedestrian facilities shall be adjacent to the project site and provide safe, accessible routes that replicate as nearly as practical the most desirable characteristics of the existing facility. Covered walkways shall be provided where pedestrians are exposed to potential injury from falling objects. Applicant shall keep sidewalk open during construction until only when it is absolutely required to close or block sidewalk for construction staging. Sidewalk shall be reopened as soon as reasonably feasible taking construction and construction staging into account.

Enforcement Agency: Los Angeles Department of Building and Safety, Los Angeles Department of Transportation

Monitoring Agency: Los Angeles Department of Building and Safety

Monitoring Phase: Construction

Monitoring Frequency: Ongoing during construction

Action Indicating Compliance: Issuance of Certificate of Occupancy or Land Use Permit

Mandatory Findings of Significance

XVIII-10 Cumulative Impacts

There may be environmental impacts which are individually limited, but significant when viewed in connection with the effects of past projects, other current projects, and probable future projects. However, these cumulative impacts will be mitigated to a less than significant level though compliance with the above mitigation measures.

XVIII-20 Effects on Human Beings

The project has potential environmental effects which cause substantial adverse effects on human beings, either directly or indirectly. However, these potential impacts will be mitigated to a less than significant level through compliance with the above mitigation measures.

XVIII-30 End

The conditions outlined in this proposed mitigated negative declaration which are not already

required by law shall be required as condition(s) of approval by the decision-making body except as noted on the face page of this document. Therefore, it is concluded that no significant impacts are apparent which might result from this project's implementation.

Regulatory Compliance Measures

In addition to the Mitigation Measures required of the project, and any proposed Project Design Features, the applicant shall also adhere to any applicable Regulatory Compliance Measures required by law. Listed below is a list of often required Regulatory Compliance Measures. Please note that requirements are determined on a case by case basis, and these are an example of the most often required Regulatory Compliance Measures.

AESTHETICS

- Regulatory Compliance Measure RC-AE-1 (Hillside): Compliance with Baseline Hillside Ordinance. To ensure consistency with the Baseline Hillside Ordinance, the project shall comply with the City's Hillside Development Guidelines, including but not limited to setback requirements, residential floor area maximums, height limits, lot coverage and grading restrictions.
- Regulatory Compliance Measure RC-AE-2 (LA River): Compliance with provisions of the Los Angeles River Improvement Overlay District. The project shall comply with development regulations set forth in Section 13.17.F of the Los Angeles Municipal Code as applicable, including but not necessarily limited to, landscaping, screening/fencing, and exterior site lighting.
- Regulatory Compliance Measure RC-AE-3 (Vandalism): Compliance with provisions of the Los Angeles Building Code. The project shall comply with all applicable building code requirements, including the following:
 - Every building, structure, or portion thereof, shall be maintained in a safe and sanitary condition and good repair, and free from, debris, rubbish, garbage, trash, overgrown vegetation or other similar material, pursuant to Municipal Code Section 91.8104.
 - The exterior of all buildings and fences shall be free from graffiti when such graffiti is visible from a street or alley, pursuant to Municipal Code Section 91.8104.15.
- Regulatory Compliance Measure RC-AE-4 (Signage): Compliance with provisions of the Los Angeles Building Code. The project shall comply with the Los Angeles Municipal Code Section 91.6205, including on-site signage maximums and multiple temporary sign restrictions, as applicable.
- Regulatory Compliance Measure RC-AE-5 (Signage on Construction Barriers): Compliance with provisions of the Los Angeles Building Code. The project shall comply with the Los Angeles Municipal Code Section 91.6205, including but not limited to the following provisions:
 - The applicant shall affix or paint a plainly visible sign, on publically accessible portions of the construction barriers, with the following language: "POST NO BILLS".
 - Such language shall appear at intervals of no less than 25 feet along the length of the publically accessible portions of the barrier.

• The applicant shall be responsible for maintaining the visibility of the required signage and for maintaining the construction barrier free and clear of any unauthorized signs within 48 hours of occurrence.

AGRICULTURE and FORESTRY

AIR QUALITY

- Regulatory Compliance Measure RC-AQ-1(Demolition, Grading and Construction Activities): Compliance with provisions of the SCAQMD District Rule 403. The project shall comply with all applicable standards of the Southern California Air Quality Management District, including the following provisions of District Rule 403:
 - All unpaved demolition and construction areas shall be wetted at least twice daily during excavation and construction, and temporary dust covers shall be used to reduce dust emissions and meet SCAQMD District Rule 403. Wetting could reduce fugitive dust by as much as 50 percent.
 - The construction area shall be kept sufficiently dampened to control dust caused by grading and hauling, and at all times provide reasonable control of dust caused by wind.
 - All clearing, earth moving, or excavation activities shall be discontinued during periods of high winds (i.e., greater than 15 mph), so as to prevent excessive amounts of dust.
 - All dirt/soil loads shall be secured by trimming, watering or other appropriate means to prevent spillage and dust.
 - All dirt/soil materials transported off-site shall be either sufficiently watered or securely covered to prevent excessive amount of dust.
 - General contractors shall maintain and operate construction equipment so as to minimize exhaust emissions.
 - Trucks having no current hauling activity shall not idle but be turned off.
- **Regulatory Compliance Measure RC-AQ-2:** In accordance with Sections 2485 in Title 13 of the California Code of Regulations, the idling of all diesel-fueled commercial vehicles (weighing over 10,000 pounds) during construction shall be limited to five minutes at any location.
- **Regulatory Compliance Measure RC-AQ-3:** In accordance with Section 93115 in Title 17 of the California Code of Regulations, operation of any stationary, diesel-fueled, compression-ignition engines shall meet specified fuel and fuel additive requirements and emission standards.
- **Regulatory Compliance Measure RC-AQ-4:** The Project shall comply with South Coast Air Quality Management District Rule 1113 limiting the volatile organic compound content of architectural coatings.
- **Regulatory Compliance Measure RC-AQ-5:** The Project shall install odor-reducing equipment in accordance with South Coast Air Quality Management District Rule 1138.

- **Regulatory Compliance Measure RC-AQ-6:** New on-site facility nitrogen oxide emissions shall be minimized through the use of emission control measures (e.g., use of best available control technology for new combustion sources such as boilers and water heaters) as required by South Coast Air Quality Management District Regulation XIII, New Source Review.
- Regulatory Compliance Measure RC-AQ-7 (Spray Painting): Compliance with provisions of the SCAQMD District Rule 403. The project shall comply with all applicable rules of the Southern California Air Quality Management District, including the following:
 - All spray painting shall be conducted within an SCAQMD-approved spray paint booth featuring approved ventilation and air filtration system.
 - Prior to the issuance of a building permit, use of land, or change of use to permit spray painting, certification of compliance with SCAQMD air pollution regulations shall be submitted to the Department of Building and Safety.
- **Regulatory Compliance Measure RC-AQ-8 (Wireless Facilities):**If rated higher than 50 brake horsepower (bhp), permit required in accordance with SCAQMD Rule 1470 Requirements for Stationary Diesel-Fueled Internal Combustion and Other Compression Initial Engines and SCAQMD Rule 1110.2 Emissions from Gaseous- and Liquid- Field Engines.

BIOLOGY

- (Duplicate of WQ Measure) Regulatory Compliance Measure RC-WQ-5 (Alteration of a State or Federal Watercourse): The project shall comply with the applicable sections of the federal Clean Water Act (CWA) and California's Porter Cologne Water Quality Control Act (Porter Cologne). Prior to the issuance of any grading, use of land, or building permit which may affect an existing watercourse, the applicant shall consult with the following agencies and obtain all necessary permits and/or authorizations, to the satisfaction of the Department of Building and Safety. Compliance shall be determined through written communication from each jurisdictional agency, a copy of which shall be submitted to the Environmental Review case file for reference:
 - United States Army Corps of Engineers. The applicant shall obtain a Jurisdictional Determination (preliminary or approved), or a letter otherwise indicating that no permit is required. Contact: Aaron O. Allen, Chief - North Coast Branch, Regulatory Division, 805-585-2148.
 - State Water Resources Control Board. The applicant shall consult with the 401 Certification and Wetlands Unit and obtain all necessary permits and/or authorizations, or a letter otherwise indicating that no permit is required. Contact: 401 Certification and Wetlands Unit, Los Angeles Region, 320 W 4th Street, #200, Los Angeles, CA 90013, (213) 576-6600.
 - California Department of Fish and Wildlife. The applicant shall consult with the Lake and Streambed Alteration Agreement Program and obtain a Streambed Alteration Agreement, or a letter otherwise indicating that no permit is required. Contact: LSAA Program, 4949 Viewridge Avenue, San Diego, CA 92123, (858) 636-3160.

CULTURAL RESOURCES

- Regulatory Compliance Measure RC-CR-1 (Designated Historic-Cultural Resource): Compliance with United States Department of the Interior – National Park Service – Secretary of the Interior's Standards for the Treatment of Historic Properties. The project shall comply with the Secretary of the Interior's Standards for Historical Resources, including but not limited to the following measures:
 - Prior to the issuance of any permit, the project shall obtain clearance from the Department of Cultural Affairs for the proposed work.
 - A property shall be used for its historic purpose or be placed in a new use that requires minimal change to the defining characteristics of the building and its site and environment.
 - The historic character of a property shall be retained and preserved. The removal of historic material or alteration of features and spaces shall be avoided.
 - Each property shall be recognized as a physical record of its time, place and use. Changes that create a false sense of historical development, such as adding conjectural features or elements from other buildings, shall not be undertaken.
 - Most properties change over time; those changes that have acquired significance in their own right shall be retained and preserved.
- **Regulatory Compliance Measure RC-CR-2 (Archaeological):** If archaeological resources are discovered during excavation, grading, or construction activities, work shall cease in the area of the find until a qualified archaeologist has evaluated the find in accordance with federal, State, and local guidelines, including those set forth in California Public Resources Code Section 21083.2. Personnel of the proposed Modified Project shall not collect or move any archaeological materials and associated materials. Construction activity may continue unimpeded on other portions of the Project site. The found deposits would be treated in accordance with federal, State, and local guidelines, including those set forth in California Public Resources of the Project site. The found deposits would be treated in accordance with federal, State, and local guidelines, including those set forth in California Public Resources Code Section 21083.2.
 - Distinctive features, finishes and construction techniques or examples of skilled craftsmanship which characterize an historic property shall be preserved.
 - Deteriorated historic features shall be repaired rather than replaced. Where the severity if deterioration requires replacement of a distinctive historic feature, the new feature shall match the old in design, color, texture, and other visual qualities, and where possible, materials. Replacement of missing features shall be substantiated by documentary, physical, or pictorial evidence.
 - Chemical or physical treatments, such as sandblasting, that cause damage to historic materials shall not be used. The surface cleaning of structures, if appropriate, shall be undertaken using the gentlest means possible.
 - Significant archaeological resources affected by a project shall be protected and preserved. If such resources must be disturbed, mitigation measures shall be undertaken.
 - New additions, exterior alterations, or related new construction shall not destroy historic materials that characterize the property. The new work shall be differentiated from the old and shall be compatible with the massing, size, scale, and architectural features to protect the historic integrity of the property and its environment.

- New additions and adjacent or related new construction shall be undertaken in such a manner that if removed in the future, the essential form and integrity of the historic property and its environment would be unimpaired.
- **Regulatory Compliance Measure RC-CR-3 (Paleontological):** If paleontological resources are discovered during excavation, grading, or construction, the City of Los Angeles Department of Building and Safety shall be notified immediately, and all work shall cease in the area of the find until a qualified paleontologist evaluates the find. Construction activity may continue unimpeded on other portions of the Project site. The paleontologist shall determine the location, the time frame, and the extent to which any monitoring of earthmoving activities shall be required. The found deposits would be treated in accordance with federal, State, and local guidelines, including those set forth in California Public Resources Code Section 21083.2.
- **Regulatory Compliance Measure CR-4 (Human Remains):** If human remains are encountered unexpectedly during construction demolition and/or grading activities, State Health and Safety Code Section 7050.5 requires that no further disturbance shall occur until the County Coroner has made the necessary findings as to origin and disposition pursuant to California Public Resources Code (PRC) Section 5097.98. In the event that human remains are discovered during excavation activities, the following procedure shall be observed:
 - Stop immediately and contact the County Coroner: 1104 N. Mission Road Los Angeles, CA 90033 323-343-0512 (8 a.m. to 5 p.m. Monday through Friday) or 323-343-0714 (After Hours, Saturday, Sunday, and Holidays)

If the remains are determined to be of Native American descent, the Coroner has 24 hours to notify the Native American Heritage Commission (NAHC).

The NAHC will immediately notify the person it believes to be the most likely descendent of the deceased Native American.

- The most likely descendent has 48 hours to make recommendations to the owner, or representative, for the treatment or disposition, with proper dignity, of the human remains and grave goods.
- If the owner does not accept the descendant's recommendations, the owner or the descendent may request mediation by the NAHC.

GEOLOGY AND SOILS

- **Regulatory Compliance Measure RC-GEO-1 (Seismic):** The design and construction of the project shall conform to the California Building Code seismic standards as approved by the Department of Building and Safety.
- **Regulatory Compliance Measure RC-GEO-2 (Hillside Grading Area):** The grading plan shall conform with the City's Landform Grading Manual guidelines, subject to approval by the Advisory Agency and the Department of Building and Safety's Grading Division.

Appropriate erosion control and drainage devices shall be provided to the satisfaction of the Building and Safety Department. These measures include interceptor terraces, berms, veechannels, and inlet and outlet structures, as specified by Section 91.7013 of the Building Code, including planting fast-growing annual and perennial grasses in areas where construction is not immediately planned.

- **Regulatory Compliance Measure RC-GEO-3 (Landslide Area):** Prior to the issuance of grading or building permits, the applicant shall submit a geotechnical report, prepared by a registered civil engineer or certified engineering geologist, to the Department of Building and Safety, for review and approval. The geotechnical report shall assess potential consequences of any landslide and soil displacement, estimation of settlement, lateral movement or reduction in foundation soil-bearing capacity, and discuss mitigation measures that may include building design consideration. Building design considerations shall include, but are not limited to:
 - ground stabilization
 - selection of appropriate foundation type and depths
 - selection of appropriate structural systems to accommodate anticipated displacements or any combination of these measures

The project shall comply with the conditions contained within the Department of Building and Safety's Geology and Soils Report Approval Letter for the proposed project, and as it may be subsequently amended or modified.

- **Regulatory Compliance Measure RC-GEO-4 (Liquefaction Area):** The project shall comply with the Uniform Building Code Chapter 18. Division1 Section 1804.5 Liquefaction Potential and Soil Strength Loss. Prior to the issuance of grading or building permits, the applicant shall submit a geotechnical report, prepared by a registered civil engineer or certified engineering geologist, to the Department of Building and Safety, for review and approval. The geotechnical report shall assess potential consequences of any liquefaction and soil strength loss, estimation of settlement, lateral movement or reduction in foundation soilbearing capacity, and discuss mitigation measures that may include building design consideration. Building design considerations shall include, but are not limited to:
 - ground stabilization
 - selection of appropriate foundation type and depths
 - selection of appropriate structural systems to accommodate anticipated displacements or any combination of these measures.

The project shall comply with the conditions contained within the Department of Building and Safety's Geology and Soils Report Approval Letter for the proposed project, and as it may be subsequently amended or modified.

• **Regulatory Compliance Measure RC-GEO-5 (Subsidence Area):** Prior to the issuance of building or grading permits, the applicant shall submit a geotechnical report prepared by a registered civil engineer or certified engineering geologist to the written satisfaction of the Department of Building and Safety. The geotechnical report shall assess potential consequences of any subsidence and soil strength loss, estimation of settlement, lateral movement or reduction in foundation soil-bearing capacity, and discuss mitigation measures that may include building design consideration. Building design considerations shall include, but are not limited to: ground stabilization, selection of appropriate foundation type and depths, selection of appropriate structural systems to accommodate anticipated displacements or any combination of these measures. The project shall comply with the conditions

contained within the Department of Building and Safety's Geology and Soils Report Approval Letter for the proposed project, and as it may be subsequently amended or modified.

- **Regulatory Compliance Measure RC-GEO-6 (Expansive Soils Area):** Prior to the issuance of grading or building permits, the applicant shall submit a geotechnical report, prepared by a registered civil engineer or certified engineering geologist, to the Department of Building and Safety, for review and approval. The geotechnical report shall assess potential consequences of any soil expansion and soil strength loss, estimation of settlement, lateral movement or reduction in foundation soil-bearing capacity, and discuss mitigation measures that may include building design consideration. Building design considerations shall include, but are not limited to: ground stabilization, selection of appropriate foundation type and depths, selection of appropriate structural systems to accommodate anticipated displacements or any combination of these measures. The project shall comply with the conditions contained within the Department of Building and Safety's Geology and Soils Report Approval Letter for the proposed project, and as it may be subsequently amended or modified.
- **Regulatory Compliance Measure RC-GHG-1 (Green Building Code):** In accordance with the City of Los Angeles Green Building Code (Chapter IX, Article 9, of the Los Angeles Municipal Code), the Project shall comply with all applicable mandatory provisions of the 2013 Los Angeles Green Code and as it may be subsequently amended or modified.

HAZARDS AND HAZARDOUS MATERIALS

- Regulatory Compliance Measure RC-HAZ-1: Explosion/Release (Existing Toxic/Hazardous Construction Materials)
 - (Asbestos) Prior to the issuance of any permit for the demolition or alteration of the existing structure(s), the applicant shall provide a letter to the Department of Building and Safety from a qualified asbestos abatement consultant indicating that no Asbestos-Containing Materials (ACM) are present in the building. If ACMs are found to be present, it will need to be abated in compliance with the South Coast Air Quality Management District's Rule 1403 as well as all other applicable State and Federal rules and regulations.
 - (Lead Paint) Prior to issuance of any permit for the demolition or alteration of the existing structure(s), a lead-based paint survey shall be performed to the written satisfaction of the Department of Building and Safety. Should lead-based paint materials be identified, standard handling and disposal practices shall be implemented pursuant to OSHA regulations.
 - (Polychlorinated Biphenyl Commercial and Industrial Buildings) Prior to issuance of a demolition permit, a polychlorinated biphenyl (PCB) abatement contractor shall conduct a survey of the project site to identify and assist with compliance with applicable state and federal rules and regulation governing PCB removal and disposal.
- Regulatory Compliance Measure RC-HAZ-2: Explosion/Release (Methane Zone): As the Project Site is within a methane zone, prior to the issuance of a building permit, the Site shall be independently analyzed by a qualified engineer, as defined in Ordinance No. 175,790

and Section 91.7102 of the LAMC, hired by the Project Applicant. The engineer shall investigate and design a methane mitigation system in compliance with the LADBS Methane Mitigation Standards for the appropriate Site Design Level which will prevent or retard potential methane gas seepage into the building. The Applicant shall implement the engineer's design recommendations subject to DOGGR, LADBS and LAFD plan review and approval.

- Regulatory Compliance Measure RC-HAZ-3: Explosion/Release (Soil Gases): During subsurface excavation activities, including borings, trenching and grading, OSHA worker safety measures shall be implemented as required to preclude any exposure of workers to unsafe levels of soil-gases, including, but not limited to, methane.
- **Regulatory Compliance Measure RC-HAZ-4 Listed Sites (Removal of Underground Storage Tanks):** Underground Storage Tanks shall be decommissioned or removed as determined by the Los Angeles City Fire Department Underground Storage Tank Division. If any contamination is found, further remediation measures shall be developed with the assistance of the Los Angeles City Fire Department and other appropriate State agencies. Prior to issuance of a use of land or building permit, a letter certifying that remediation is complete from the appropriate agency (Department of Toxic Substance Control or the Regional Water Quality Control Board) shall be submitted to the decision maker.
- **Regulatory Compliance Measure RC-HAZ-5 (Hazardous Materials Site):** Prior to the issuance of any use of land, grading, or building permit, the applicant shall obtain a sign-off from the Fire Department indicating that all on-site hazardous materials, including contamination of the soil and groundwater, have been suitably remediated, or that the proposed project will not impede proposed or on-going remediation measures.

HYDROLOGY AND WATER QUALITY

- Regulatory Compliance Measure RC-WQ-1: National Pollutant Discharge Elimination System General Permit. Prior to issuance of a grading permit, the Applicant shall obtain coverage under the State Water Resources Control Board National Pollutant Discharge Elimination System General Permit for Storm Water Discharges Associated with Construction and Land Disturbance Activities (Order No. 2009-0009-DWQ, National Pollutant Discharge Elimination System No. CAS000002) (Construction General Permit) for Phase 1 of the proposed Modified Project. The Applicant shall provide the Waste Discharge Identification Number to the City of Los Angeles to demonstrate proof of coverage under the Construction General Permit. A Storm Water Pollution Prevention Plan shall be prepared and implemented for the proposed Modified Project in compliance with the requirements of the Construction General Permit. The Storm Water Pollution Prevention Plan shall identify construction Best Management Practices to be implemented to ensure that the potential for soil erosion and sedimentation is minimized and to control the discharge of pollutants in stormwater runoff as a result of construction activities.
- **Regulatory Compliance Measure RC-WQ-2: Dewatering.** If required, any dewatering activities during construction shall comply with the requirements of the Waste Discharge Requirements for Discharges of Groundwater from Construction and Project Dewatering to Surface Waters in Coastal Watersheds of Los Angeles and Ventura Counties (Order No. R4-2008-0032, National Pollutant Discharge Elimination System No. CAG994004) or

subsequent permit. This will include submission of a Notice of Intent for coverage under the permit to the Los Angeles Regional Water Quality Control Board at least 45 days prior to the start of dewatering and compliance with all applicable provisions in the permit, including water sampling, analysis, and reporting of dewatering-related discharges.

- **Regulatory Compliance Measure RC-WQ-3: Low Impact Development Plan.** Prior to issuance of grading permits, the Applicant shall submit a Low Impact Development Plan and/or Standard Urban Stormwater Mitigation Plan to the City of Los Angeles Bureau of Sanitation Watershed Protection Division for review and approval. The Low Impact Development Plan and/or Standard Urban Stormwater Mitigation Plan shall be prepared consistent with the requirements of the Development Best Management Practices Handbook.
- **Regulatory Compliance Measure RC-WQ-4: Development Best Management Practices.** The Best Management Practices shall be designed to retain or treat the runoff from a storm event producing 0.75 inch of rainfall in a 24-hour period, in accordance with the Development Best Management Practices Handbook Part B Planning Activities. A signed certificate from a licensed civil engineer or licensed architect confirming that the proposed Best Management Practices meet this numerical threshold standard shall be provided.
- Regulatory Compliance Measure RC-WQ-5 (Alteration of a State or Federal Watercourse): The project shall comply with the applicable sections of the federal Clean Water Act (CWA) and California's Porter Cologne Water Quality Control Act (Porter Cologne). Prior to the issuance of any grading, use of land, or building permit which may affect an existing watercourse, the applicant shall consult with the following agencies and obtain all necessary permits and/or authorizations, to the satisfaction of the Department of Building and Safety. Compliance shall be determined through written communication from each jurisdictional agency, a copy of which shall be submitted to the Environmental Review case file for reference:
 - United States Army Corps of Engineers. The applicant shall obtain a Jurisdictional Determination (preliminary or approved), or a letter otherwise indicating that no permit is required. Contact: Aaron O. Allen, Chief - North Coast Branch, Regulatory Division, 805-585-2148.
 - State Water Resources Control Board. The applicant shall consult with the 401 Certification and Wetlands Unit and obtain all necessary permits and/or authorizations, or a letter otherwise indicating that no permit is required. Contact: 401 Certification and Wetlands Unit, Los Angeles Region, 320 W 4th Street, #200, Los Angeles, CA 90013, (213) 576-6600.
 - California Department of Fish and Wildlife. The applicant shall consult with the Lake and Streambed Alteration Agreement Program and obtain a Streambed Alteration Agreement, or a letter otherwise indicating that no permit is required. Contact: LSAA Program, 4949 Viewridge Avenue, San Diego, CA 92123, (858) 636-3160.
- **Regulatory Compliance Measure RC-WQ-6 (Flooding/Tidal Waves):** The project shall comply with the requirements of the Flood Hazard Management Specific Plan, Ordinance No. 172081 effective 7/3/98.

LAND USE AND PLANNING

• **Regulatory Compliance Measure RC-LU-1 (Slope Density):** The project shall not exceed the maximum density permitted in Hillside Areas, as calculated by the formula set forth in Los Angeles Municipal Code Section 17.05-C (for tracts) or 17.50-E (for parcel maps).

MINERAL RESOURCES

NOISE

• Regulatory Compliance Measure RC-NO-1 (Demolition, Grading, and Construction Activities): The project shall comply with the City of Los Angeles Noise Ordinance and any subsequent ordinances, which prohibit the emission or creation of noise beyond certain levels at adjacent uses unless technically infeasible.

POPULATION AND HOUSING

- New Regulatory Compliance Measure RC-PH-1 (Tenant Displacement):
 - Apartment Converted to Condominium Prior to final map recordation, and pursuant to the provisions of Section 12.95.2-G and 47.06 of the Los Angeles Municipal Code (LAMC), a tenant relocation plan shall be submitted to the Los Angeles Housing Department for review and approval.
 - Apartment Demolition Prior to the issuance of a demolition permit, and pursuant to the provisions of Section 47.07 of the Los Angeles Municipal Code, a tenant relocation plan shall be submitted to the Los Angeles Housing Department for review and approval.
 - **Mobile Home Park Closure or Conversion to Different Use** Prior to the issuance of any permit or recordation, and pursuant to the provisions of Section 47.08 and 47.09 of the Los Angeles Municipal Code, a tenant relocation plan and mobile home park closure impact report shall be submitted to the Los Angeles Housing Department for review and approval.

PUBLIC SERVICES

Schools

• **Regulatory Compliance Measure RC-PS-1 (Payment of School Development Fee)** Prior to issuance of a building permit, the General Manager of the City of Los Angeles, Department of Building and Safety, or designee, shall ensure that the Applicant has paid all applicable school facility development fees in accordance with California Government Code Section 65995.

Parks

- Regulatory Compliance Measure RC-PS-2 (Increased Demand For Parks Or Recreational Facilities):
 - (Subdivision) Pursuant to Section 17.12-A or 17.58 of the Los Angeles Municipal Code, the applicant shall pay the applicable Quimby fees for the construction of dwelling units.

- (*Apartments*) Pursuant to Section 21.10 of the Los Angeles Municipal Code, the applicant shall pay the Dwelling Unit Construction Tax for construction of apartment buildings.
- Regulatory Compliance Measure RC-PS-3 (Increase Demand For Parks Or Recreational Facilities Zone Change) Pursuant to Section 12.33 of the Los Angeles Municipal Code, the applicant shall pay the applicable fees for the construction of dwelling units.

RECREATION

See RC measures above under Parks.

TRANSPORTATION AND TRAFFIC

• Regulatory Compliance Measure RC-TT-1 (Increased Vehicle Trips/Congestion - West Side Traffic Fee) Prior to issuance of a Building Permit, the applicant shall pay a traffic impact fee to the City, based on the requirements of the West Los Angeles Traffic Improvement and Mitigation Specific Plan (WLA TIMP).

PUBLIC UTILITIES AND SERVICE SYSTEMS

Water Supply

- **Regulatory Compliance Measure RC-WS-1 (Fire Water Flow)** The Project Applicant shall consult with the LADBS and LAFD to determine fire flow requirements for the Proposed Project, and will contact a Water Service Representative at the LADWP to order a SAR. This system hydraulic analysis will determine if existing LADWP water supply facilities can provide the proposed fire flow requirements of the Project. If water main or infrastructure upgrades are required, the Applicant would pay for such upgrades, which would be constructed by either the Applicant or LADWP.
- **Regulatory Compliance Measure RC-WS-2 (Green Building Code):** The Project shall implement all applicable mandatory measures within the LA Green Building Code that would have the effect of reducing the Project's water use.
- **Regulatory Compliance Measure RC-WS-3 (New Carwash):** The applicant shall incorporate a water recycling system to the satisfaction of the Department of Building and Safety.
- **Regulatory Compliance Measure RC-WS-4 (Landscape)** The Project shall comply with Ordinance No. 170,978 (Water Management Ordinance), which imposes numerous water conservation measures in landscape, installation, and maintenance (e.g., use drip irrigation and soak hoses in lieu of sprinklers to lower the amount of water lost to evaporation and overspray, set automatic sprinkler systems to irrigate during the early morning or evening hours to minimize water loss due to evaporation, and water less in the cooler months and during the rainy season).

Energy

• **Regulatory Compliance Measure RC-EN-1(Green Building Code):** The Project shall implement all applicable mandatory measures within the LA Green Building Code that would have the effect of reducing the Project's energy use.

Solid Waste

- **Regulatory Compliance Measure RC-SW-1 (Designated Recycling Area)** In compliance with Los Angeles Municipal Code, the proposed Modified Project shall provide readily accessible areas that serve the entire building and are identified for the depositing, storage, and collection of nonhazardous materials for recycling, including (at a minimum) paper, corrugated cardboard, glass, plastics, and metals.
- Regulatory Compliance Measure RC-SW-2 (Construction Waste Recycling) In order to meet the diversion goals of the California Integrated Waste Management Act and the City of Los Angeles, which will total 70 percent by 2013, the Applicant shall salvage and recycle construction and demolition materials to ensure that a minimum of 70 percent of construction-related solid waste that can be recycled is diverted from the waste stream to be landfilled. Solid waste diversion would be accomplished though the on-site separation of materials and/or by contracting with a solid waste disposal facility that can guarantee a minimum diversion rate of 70 percent. In compliance with the Los Angeles Municipal Code, the General Contractor shall utilize solid waste haulers, contractors, and recyclers who have obtained an Assembly Bill (AB) 939 Compliance Permit from the City of Los Angeles Bureau of Sanitation.
- Regulatory Compliance Measure RC-SW-3 (Commercial/Multifamily Mandatory Recycling) In compliance with AB341, recycling bins shall be provided at appropriate locations to promote recycling of paper, metal, glass and other recyclable material. These bins shall be emptied and recycled accordingly as a part of the Proposed Project's regular solid waste disposal program. The Project Applicant shall only contract for waste disposal services with a company that recycles solid waste in compliance with AB341.