

filed 1/17/14

CITY OF LOS ANGELES
OFFICE OF THE CITY CLERK
ROOM 395, CITY HALL
LOS ANGELES, CALIFORNIA 90012
CALIFORNIA ENVIRONMENTAL QUALITY ACT
PROPOSED MITIGATED NEGATIVE DECLARATION

LEAD CITY AGENCY
City of Los Angeles

COUNCIL DISTRICT
CD 5 - PAUL KORETZ

PROJECT TITLE
ENV-2013-3734-MND

CASE NO.
VTT-72465-SL, ZA-2013-3735-ZAA

PROJECT LOCATION
11767 EAST BELLAGIO ROAD, BEL AIR-BEVERLY CREST, 90049

PROJECT DESCRIPTION
The proposed project involves the demolition of an existing one-story single-family dwelling in conjunction with the construction of six new for-sale single-family dwellings on a 7,853 net square-foot (0.18 acres) lot in the Bel Air-Beverly Crest neighborhood of Los Angeles. The proposed dwellings will be three stories within a maximum height of 41 feet and will range in size from 2,250 to 2,541 square feet of floor area and will be comprised of three-bedroom configurations atop a private two-car garage. Each lot is on average 1,300 square feet. The new development will total approximately 14,442 square feet of living area and will provide 12 parking spaces within private garages in the [Q]RD1.5-1VL Zone.

Requested entitlements include: the subdivision of land through a Vesting Tentative Tract Map process creating six ground lots (Lots 1 through 6) containing six single-family dwellings; a Zone Variance to allow zero square feet of open space in lieu of the required 1,050 square feet (175 square feet per unit) in the [Q]RD1.5-1VL Zone; and Zoning Administrator's Adjustments to permit: (a) a 5-foot front yard setback in lieu of the required 15-foot setback on Lot 5, (b) a zero-foot side yard in lieu of the required four feet for all interior side yards, (c) a zero-foot rear yard setback in lieu of the required 15 feet, (d) no building separation among the single-family dwellings in lieu of the required 12 feet, and (e) varying reduced passageways between Lots 1 and 6 and between Lots 2 and 5 in lieu of the required 12 feet.

NAME AND ADDRESS OF APPLICANT IF OTHER THAN CITY AGENCY
Steve Nazemi (Representative) DHS & Associates Inc.
275 Centennial Way, Suite 205
Tustin, CA 92780

FINDING:
The City Planning Department of the City of Los Angeles has Proposed that a mitigated negative declaration be adopted for this project because the mitigation measure(s) outlined on the attached page(s) will reduce any potential significant adverse effects to a level of insignificance
(CONTINUED ON PAGE 2)

SEE ATTACHED SHEET(S) FOR ANY MITIGATION MEASURES IMPOSED.

Any written comments received during the public review period are attached together with the response of the Lead City Agency. The project decision-maker may adopt the mitigated negative declaration, amend it, or require preparation of an EIR. Any changes made should be supported by substantial evidence in the record and appropriate findings made.

THE INITIAL STUDY PREPARED FOR THIS PROJECT IS ATTACHED.

NAME OF PERSON PREPARING THIS FORM	TITLE	TELEPHONE NUMBER
	City Planning Assistant	(213) 978-0092

ADDRESS	SIGNATURE (Official)	DATE
200 N. SPRING STREET, 7th FLOOR LOS ANGELES, CA. 90012		02/24/2014

I-10. Aesthetics (Landscape Plan)

- Environmental impacts to the character and aesthetics of the neighborhood may result from project implementation. However, the potential impacts will be mitigated to a less than significant level by the following measure:
- All open areas not used for buildings, driveways, parking areas, recreational facilities or walks shall be attractively landscaped and maintained in accordance with a landscape plan and an automatic irrigation plan, prepared by a Landscape Practitioner (Sec. 12.40-D) and to the satisfaction of the decision maker.

I-90. Aesthetics (Vandalism)

- Environmental impacts may result from project implementation due to graffiti and accumulation of rubbish and debris along the wall(s) adjacent to public rights-of-way. However, this potential impact will be mitigated to a less than significant level by the following measures:
- Every building, structure, or portion thereof, shall be maintained in a safe and sanitary condition and good repair, and free from, debris, rubbish, garbage, trash, overgrown vegetation or other similar material, pursuant to Municipal Code Section 91.8104.
- The exterior of all buildings and fences shall be free from graffiti when such graffiti is visible from a street or alley, pursuant to Municipal Code Section 91.8104.15.

I-110. Aesthetics (Signage on Construction Barriers)

- Environmental impacts may result from project implementation due to on-site signage in excess of that allowed under the Los Angeles Municipal Code Section 91.6205. However, the potential impact will be mitigated to a less than significant level by the following measures:
- The applicant shall affix or paint a plainly visible sign, on publically accessible portions of the construction barriers, with the following language: "POST NO BILLS".
- Such language shall appear at intervals of no less than 25 feet along the length of the publically accessible portions of the barrier.
- The applicant shall be responsible for maintaining the visibility of the required signage and for maintaining the construction barrier free and clear of any unauthorized signs within 48 hours of occurrence.

I-120. Aesthetics (Light)

- Environmental impacts to the adjacent residential properties may result due to excessive illumination on the project site. However, the potential impacts will be mitigated to a less than significant level by the following measure:
- Outdoor lighting shall be designed and installed with shielding, such that the light source cannot be seen from adjacent residential properties or the public right-of-way.

III-10. Air Pollution (Demolition, Grading, and Construction Activities)

-
- All unpaved demolition and construction areas shall be wetted at least twice daily during excavation and construction, and temporary dust covers shall be used to reduce dust emissions and meet SCAQMD District Rule 403. Wetting could reduce fugitive dust by as much as 50 percent.
- The construction area shall be kept sufficiently dampened to control dust caused by grading and hauling, and at all times provide reasonable control of dust caused by wind.
- All clearing, earth moving, or excavation activities shall be discontinued during periods of high winds (i.e., greater than 15 mph), so as to prevent excessive amounts of dust.
- All dirt/soil loads shall be secured by trimming, watering or other appropriate means to prevent spillage and dust.
- All dirt/soil materials transported off-site shall be either sufficiently watered or securely covered to prevent excessive amount of dust.
- General contractors shall maintain and operate construction equipment so as to minimize exhaust emissions.
- Trucks having no current hauling activity shall not idle but be turned off.

IV-20. Habitat Modification (Nesting Native Birds, Non-Hillside or Urban Areas)

- The project will result in the removal of vegetation and disturbances to the ground and therefore may result in take of nesting native bird species. Migratory nongame native bird species are protected by international treaty under the Federal Migratory Bird Treaty Act (MBTA) of 1918 (50 C.F.R Section 10.13). Sections 3503, 3503.5 and 3513 of the California Fish and Game Code prohibit take of all birds and their active nests including raptors and other migratory nongame birds (as listed under the Federal MBTA).

- Proposed project activities (including disturbances to native and non-native vegetation, structures and substrates) should take place outside of the breeding bird season which generally runs from March 1- August 31 (as early as February 1 for raptors) to avoid take (including disturbances which would cause abandonment of active nests containing eggs and/or young). Take means to hunt, pursue, catch, capture, or kill, or attempt to hunt, pursue, catch, capture or kill (Fish and Game Code Section 86).
- If project activities cannot feasibly avoid the breeding bird season, beginning thirty days prior to the disturbance of suitable nesting habitat, the applicant shall:
- Arrange for weekly bird surveys to detect any protected native birds in the habitat to be removed and any other such habitat within properties adjacent to the project site, as access to adjacent areas allows. The surveys shall be conducted by a qualified biologist with experience in conducting breeding bird surveys. The surveys shall continue on a weekly basis with the last survey being conducted no more than 3 days prior to the initiation of clearance/construction work.
- If a protected native bird is found, the applicant shall delay all clearance/construction disturbance activities within 300 feet of suitable nesting habitat for the observed protected bird species until August 31.
- Alternatively, the Qualified Biologist could continue the surveys in order to locate any nests. If an active nest is located, clearing and construction within 300 feet of the nest or as determined by a qualified biological monitor, shall be postponed until the nest is vacated and juveniles have fledged and when there is no evidence of a second attempt at nesting. The buffer zone from the nest shall be established in the field with flagging and stakes. Construction personnel shall be instructed on the sensitivity of the area.
- The applicant shall record the results of the recommended protective measures described above to document compliance with applicable State and Federal laws pertaining to the protection of native birds. Such record shall be submitted and received into the case file for the associated discretionary action permitting the project.

IV-70. Tree Removal (Non-Protected Trees)

- Environmental impacts from project implementation may result due to the loss of significant trees on the site. However, the potential impacts will be mitigated to a less than significant level by the following measures:
- Prior to the issuance of any permit, a plot plan shall be prepared indicating the location, size, type, and general condition of all existing trees on the site and within the adjacent public right(s)-of-way.
- All significant (8-inch or greater trunk diameter, or cumulative trunk diameter if multi-trunked, as measured 54 inches above the ground) non-protected trees on the site proposed for removal shall be replaced at a 1:1 ratio with a minimum 24-inch box tree. Net, new trees, located within the parkway of the adjacent public right(s)-of-way, may be counted toward replacement tree requirements.
- Removal or planting of any tree in the public right-of-way requires approval of the Board of Public Works. Contact Urban Forestry Division at: 213-847-3077. All trees in the public right-of-way shall be provided per the current standards of the Urban Forestry Division the Department of Public Works, Bureau of Street Services.
- If trees are removed from the site, replacement trees shall be at least 15-gallon-sized per the Tree Report prepared on August 28, 2013 by Shelley Sparks, RLA.

VI-10. Seismic

- Environmental impacts to the safety of future occupants may result due to the project's location in an area of potential seismic activity. However, this potential impact will be mitigated to a less than significant level by the following measure:
- The design and construction of the project shall conform to the California Building Code seismic standards as approved by the Department of Building and Safety.

VI-20. Erosion/Grading/Short-Term Construction Impacts

- Short-term erosion impacts may result from the construction of the proposed project. However, these impacts can be mitigated to a less than significant level by the following measures:
- The applicant shall provide a staked signage at the site with a minimum of 3-inch lettering containing contact information for the Senior Street Use Inspector (Department of Public Works), the Senior Grading Inspector (LADBS) and the hauling or general contractor.
- Chapter IX, Division 70 of the Los Angeles Municipal Code addresses grading, excavations, and fills. All grading activities require grading permits from the Department of Building and Safety. Additional provisions are required for grading activities within Hillside areas. The application of BMPs includes but is not limited to the following mitigation measures:

- a. Excavation and grading activities shall be scheduled during dry weather periods. If grading occurs during the rainy season (October 15 through April 1), diversion dikes shall be constructed to channel runoff around the site. Channels shall be lined with grass or roughened pavement to reduce runoff velocity.
- b. Stockpiles, excavated, and exposed soil shall be covered with secured tarps, plastic sheeting, erosion control fabrics, or treated with a bio-degradable soil stabilizer.

VI-30. Erosion/Grading/Short-Term Construction Impacts (Hillside Grading Areas)

- Environmental impacts may result from the visual alteration of natural landforms due to grading. However, this impact will be mitigated to a less than significant level by the following measures:
- The grading plan shall conform with the City's Landform Grading Manual guidelines, subject to approval by the Advisory Agency and the Department of Building and Safety's Grading Division.
- Appropriate erosion control and drainage devices shall be provided to the satisfaction of the Building and Safety Department. These measures include interceptor terraces, berms, vee-channels, and inlet and outlet structures, as specified by Section 91.7013 of the Building Code, including planting fast-growing annual and perennial grasses in areas where construction is not immediately planned.

VI-50. Geotechnical Report

-
- Prior to the issuance of grading or building permits, the applicant shall submit a geotechnical report, prepared by a registered civil engineer or certified engineering geologist, to the Department of Building and Safety, for review and approval. The geotechnical report shall assess potential consequences of any soil strength loss, estimation of settlement, lateral movement or reduction in foundation soil-bearing capacity, and discuss mitigation measures that may include building design consideration. Building design considerations shall include, but are not limited to: ground stabilization, selection of appropriate foundation type and depths, selection of appropriate structural systems to accommodate anticipated displacements or any combination of these measures.
- The project shall comply with the conditions contained within the Department of Building and Safety's Geology and Soils Report Approval Letter for the proposed project, and as it may be subsequently amended or modified.

VI-70. Liquefaction Area

- Environmental impacts may result due to the proposed project's location in an area with liquefaction potential. However, these potential impacts will be mitigated to a less than significant level by the following measures:
- The project shall comply with the conditions contained within the Department of Building and Safety's Geology and Soils Report Approval Letter for the proposed project, and as it may be subsequently amended or modified.

VII-10. Green House Gas Emissions

- The project will result in impacts resulting in increased green house gas emissions. However, the impact can be reduced to a less than significant level though compliance with the following measure(s):
- Only low- and non-VOC-containing paints, sealants, adhesives, and solvents shall be utilized in the construction of the project.

VIII-10. Explosion/Release (Existing Toxic/Hazardous Construction Materials)

- Due to the age of the building(s) being demolished, toxic and/or hazardous construction materials may be located in the structure(s). Exposure to such materials during demolition or construction activities could be hazardous to the health of the demolition workers, as well as area residents, employees, and future occupants. However, these impacts can be mitigated to a less than significant level by the following measure:
- **(Asbestos)** Prior to the issuance of any permit for the demolition or alteration of the existing structure(s), the applicant shall provide a letter to the Department of Building and Safety from a qualified asbestos abatement consultant indicating that no Asbestos-Containing Materials (ACM) are present in the building. If ACMs are found to be present, it will need to be abated in compliance with the South Coast Air Quality Management District's Rule 1403 as well as all other applicable State and Federal rules and regulations.
- **(Lead Paint)** Prior to issuance of any permit for the demolition or alteration of the existing structure(s), a lead-based paint survey shall be performed to the written satisfaction of the Department of Building and Safety. Should lead-based paint materials be identified, standard handling and disposal practices shall be implemented pursuant to OSHA regulations.

VIII-40. Hillside Construction Staging and Parking Plan

-

- Prior to the issuance of a grading or building permit, the applicant shall submit a Construction Staging and Parking Plan to the Department of Building and Safety and the Fire Department for review and approval. The plan shall identify where all construction materials, equipment, and vehicles will be stored through the construction phase of the project, as well as where contractor, subcontractor, and laborers will park their vehicles so as to prevent blockage of two-way traffic on streets in the vicinity of the construction site. The Construction Staging and Parking Plan shall include, but not be limited to, the following:
- No construction equipment or material shall be permitted to be stored within the public right-of-way.
- If the property fronts on a designated Red Flag Street, on noticed "Red Flag" days, all the workers shall be shuttled from an off-site area, located on a non-Red Flag Street, to and from the site in order to keep roads open on Red Flag days.
- During the Excavation and Grading phases, only one truck hauler shall be allowed on the site at any one time. The drivers shall be required to follow the designated travel plan or approved Haul Route.
- Truck traffic directed to the project site for the purpose of delivering materials, construction-machinery, or removal of graded soil shall be limited to off-peak traffic hours, Monday through Friday only. No truck deliveries shall be permitted on Saturdays or Sundays.
- All deliveries during construction shall be coordinated so that only one vendor/delivery vehicle is at the site at one time, and that a construction supervisor is present at such time.
- A radio operator shall be on-site to coordinate the movement of material and personnel, in order to keep the roads open for emergency vehicles, their apparatus, and neighbors.
- During all phases of construction, all construction vehicle parking and queuing related to the project shall be as required to the satisfaction of the Department of Building and Safety, and in substantial compliance with the Construction Staging and Parking Plan, except as may be modified by the Department of Building and Safety or the Fire Department.

VIII-70. Emergency Evacuation Plan

- Environmental impacts may result from project implementation due to possible interference with an emergency response plan. However, these potential impacts will be mitigated to a less than significant level by the following measure:
- Prior to the issuance of a building permit, the applicant shall develop an emergency response plan in consultation with the Fire Department. The emergency response plan shall include but not be limited to the following: mapping of emergency exits, evacuation routes for vehicles and pedestrians, location of nearest hospitals, and fire departments.

X-60. Land Use/Planning

- The project will result in land use and/or planning impact(s). However, the impact(s) can be reduced to a less than significant level through compliance with the following measure(s):
- An air filtration system shall be installed and maintained with filters meeting or exceeding the ASHRAE Standard 52.2 Minimum Efficiency Reporting Value (MERV) of 11, to the satisfaction of the Department of Building and Safety.

XII-20. Increased Noise Levels (Demolition, Grading, and Construction Activities)

- The project shall comply with the City of Los Angeles Noise Ordinance No. 144,331 and 161,574, and any subsequent ordinances, which prohibit the emission or creation of noise beyond certain levels at adjacent uses unless technically infeasible.
- Construction and demolition shall be restricted to the hours of 7:00 am to 6:00 pm Monday through Friday, and 8:00 am to 6:00 pm on Saturday.
- Demolition and construction activities shall be scheduled so as to avoid operating several pieces of equipment simultaneously, which causes high noise levels.
- The project contractor shall use power construction equipment with state-of-the-art noise shielding and muffling devices.

XII-180. Increased Noise Levels (Residential within 500 feet of Freeway)

- Environmental impacts to proposed residential uses from higher ambient noise levels due to being located in close proximity to a freeway. However, this impact can be reduced to a less than significant level by the following measures:
- Wall and roof-ceiling assemblies making up the building envelope shall have an STC of at least 50, and exterior windows shall have a minimum STC of 30, as determined in accordance with ASTM E90 and ASTM E413, or any amendment thereto.

XIV-10. Public Services (Fire)